

## CRACK FILL MELTER APPLICATORS

# RY10MA-V3 BASE MODEL

The RY10MA was designed to be the most efficient, safe, reliable and easy-to-use torch fired crack fill machine. Contractors can melt and apply up to 400 feet per hour; 3,200 feet per day and features cutting edge innovations like the RynoValve™ and latching lid.



### SPECIFICATIONS

**Fluid Capacity**  
12.5 US Gallons

**Kettle Steel Thickness**  
14 Gauge

**Assembled Dimensions**  
49.1" x 27.5" x 36.7"

**Empty Weight**  
141.8 lbs / 64.6 kg

**Max Capacity Weight**  
264.3 lbs / 120.1 kg

**Fuel Type**  
Propane

**Max Fuel Pressure**  
30 psi

**Burner Type**  
150,000 BTU/hr  
Heating Torch

**Valve Type**  
1.25" RynoValve™

**Agitation Type**  
Manual

### PRODUCTIVE

- Melt and apply up to 3,200 feet of crack sealant per day.
- RynoValve™ requires virtually no preheating time and is ready to use as soon as you have hot sealant in the kettle, saving you time between jobs.

### RELIABLE

- The unique glycerin-filled thermometer is highly resistant to damage caused by constant vibrations during regular use, which ensures a reliable temperature reading every time.
- Rear wheels feature double ball bearings for increased stability and smooth operation.

### EASY TO OPERATE

- Valve control arm allows for adjusting the spring tension for optimal performance.
- Adjustable regulator includes a pressure gauge to easily monitor fuel pressure.

### SAFETY BUILT-IN

- Kettle is equipped with a latch which help keep your lid securely fastened while moving from job to job.
- Features a heavy-duty ratchet strap to secure the propane tank.