

CRACK FILL MELTER KETTLES

RY10MK

The RY10MK is a portable Crack Fill Kettle designed to be free standing or optionally bolted to any truck or trailer. Its heavy-duty molasses valve allows you to control the flow of material into any pour-pot or bander. Safety, reliability and efficiency combine in this machine to create a contractor's must-have.



SPECIFICATIONS

Fluid Capacity
10 US Gallons

Kettle Steel Thickness
14 Gauge

Assembled Dimensions
24.8" x 16.3" x 36.1"

Empty Weight
101 lbs / 45.8 kg

Max Capacity Weight
199 lbs / 90.4 kg

Fuel Type
Propane

Max Fuel Pressure
30 psi

Burner Type
150,000 BTU/hr
Heating Torch

Valve Type
2" Molasses Valve

Agitation Type
Manual

PRODUCTIVE

- Melt up to 400 feet of crack sealant per hour.
- Melt up to 3,200 feet of crack sealant per day.

RELIABLE

- The unique glycerin-filled thermometer is highly resistant to damage caused by constant vibrations during regular use, which ensures a reliable temperature reading every time.
- Built-in strainer prevents valve clogs from unmelted pieces of rubber.

EASY TO OPERATE

- 2" molasses valve quickly and conveniently dispenses melted crack filler.
- Standard manual agitation allows for easy mixing of material as it melts.

SAFETY BUILT-IN

- 1/2" holes in leg channels allow for safe and easy mounting to any truck or trailer.
- Kettle is equipped with a latch, which helps keep your lid securely fastened while moving from job to job.